



SKIOLD DISC MILLS



SKIOLD MAKES THE DIFFERENCE!

CAPACITY

Type	SK2500		SK5000			SK10T			SK780	
kW	5.5	7.5	15	22	30	55	75	90	160	200
Barley (ton/hour):	0,7-1,4	1-1,9	1,7-3,2	2,4-4,7	3-6	5-10	6-13	7-16	9-19,5	12-26
Wheat (ton/hour):	0,75-1,5	1-2	1,8-3,5	2,5-5	3,2-6,5	5-12	6-15	7-18	9-22,5	12-30
Maize (ton/hour):	0,5-1,5	0,7-2	2-3,5	2,5-5	3-6,5	5-12	6-15	7-18	9-22,5	12-30
Oats (ton/hour):	0,6-1	0,8-1,3	1,4-2,3	2-3,2	2,4-4,5	4-9	5-12	6-14	9-18	12-24
Peas (ton/hour):	0,5-1,5	0,75-2	2-3,5	2,5-5	3-6,5	4-9	5-12	6-14	9-18	12-24

TECHNICAL SPECIFICATIONS

Type	SK2500	SK5000	SK10T	SK780
Disc diameter, outer (mm):	300	450	550	780
Disc distance regulation:	Manual or automatic	Manual or automatic	Automatic	Automatic
Disc distance min./max. (mm):	0 - 10	0 - 10	0 - 8	0 - 9
Inlet, round/square (mm):	Ø100 / Ø150	Ø150	200 x 200	Ø200
Outlet, rectangular (mm):	300 x 87	482 x 101	710 x 198	945 x 295
Feeding auger:	Optional (0.37 kW)	Optional (0.75 kW)	Yes (0.75 kW)	Yes (1.5 kW)
Main bearing greasing:	Manually	Manually	Automatic	Automatic
Temperature switch:	Optional	Optional	Yes	Yes
Noise level, approx. (dB):	80	80	80	80
RPM:	3000	3000	3000	3000
Approx. weight (kg):	120	335	1100-1400	4600

In storage dry and well cleaned crops.
The capacity depends on the grinding fineness.

Data sheet: 130-986 003-960_04_13-06-2019.

SKIOLD A/S • CVR: DK 57 08 1112 Sæby • All Rights Reserved.

