



STOP SYSTEMS



Ø50,8

Ø60:

28,2+D

168+D

100

100

270

270

Ø60

SKIOLD MAKES THE DIFFERENCE!

Weight : 0,5 kg

All measures in mm.

SENSOR OVERVIEW:

Previous sensor	DOL33RR230V	DOL33RR24VAC	DOL33R230V	DOL33R24VAC
Description	With timer	With timer	With timer	With timer
Voltage	230V	24V	230V	24V
New sensor	VC11RT230 (140601070105)	VC11RT924 (140601070100)	VC12RT230 (140601070170)	VC12RT924 (140601070120)
TP0	(✓)			
TP0 M	✓			
TP1	(✓)	(✓)		
TP2	(✓)	(✓)		
TP3		(✓)		
MultiPork		✓		
Hopper			✓	✓
Ø50,8 complete	140601075088	140601075089	140601075084	140601075086
Ø60 complete	140601076008	140601076009	140601076004	140601076006
Relocatable sensor	140601070015		140601070020	

() = can be used, but is not standard. As safety sensor, use VC11RT230.



Stop systems

To identify the suitable sensor, first define the control unit and the voltage in question. After this, the pipe diameter is defined, and the item number corresponding to all 3 variables is selected

Included in the stop system are:

- 1 capacitive sensor
- 1 feed drop
- 1 tube for sensor
- 2 tube joints

All parts are supplied in a plastic bag.

When ordering relocatable sensors; please order minimum 2 mounting kits for relocatable sensors separately:

MOUNTING KIT FOR RELOCATABLE SENSOR:

Item number	140601070380	140601070450	140601070508	140601070600	140601070630
Dimension	Ø38	Ø45	Ø50,8	Ø60	Ø63,5